



product details

**44892 WFL**

Product description: 44892 WFL  
 Product code: 4050300346236  
 Quantity: Shipping carton box (VS) contains 10 Piece (PCE)

You can find this product in the eCatalog:  
[http://catalog.myosram.com?~language=EN&~country=DE&it\\_p=4050300346236](http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300346236)

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
SEG number	8326894
ILCOS	HRGS//UB-35-12-GU4-35/36

General Description	
Base (standard designation)	GU4
Mercury-free	Yes

Technical - Electrical Data	
Nominal wattage (packaging)	35 W
Construction wattage	35 W
Nominal voltage	12 V

Technical - Geometries	
Overall length	42.00 mm
Contact spacing	4 mm
Diameter	35.0 mm
Length	40.00 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Luminous intensity	1000 cd
Beam angle	36 °
Color temperature	3000 K
Color rendering index Ra	100
Rated starting time	0.0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300346229	Folding carton box contains 1 Piece	34,000 mm x 34,000 mm x 50,000 mm	18,000 g (0,000 g)	0.058 Cubic dec.
4050300346236	Shipping carton box contains 10 Piece	81,000 mm x 58,000 mm x 178,000 mm	206,750 g (0,000 g)	0.836 Cubic dec.



01.08.2011

Subject to change without notice. Errors and omission excepted.

© 2011 OSRAM AG

Page 1 of 2



product details

## 44892 WFL

Every professional knows that light is not always the same when it comes to illuminating heat-sensitive objects. In this case the DECOSTAR 35 dichroic reflector lamp is the right choice because most of the heat produced by the lamp is emitted through the rear of the reflector. This reduces the heat in the light beam by up to 66 %. It is therefore easier to present heat-sensitive objects in the right light.

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Approved for use in open luminaires to IEC 60598-1
- Average life: 2,000 h
- Dimmable
- $R_a=100$
- Color temperature: 10 W - 2,900 K; 20 W/35 W - 3,000 K
- Base: GU4
- UV filter

For light distribution curves go to [www.osram.com](http://www.osram.com)