



MASTERCcolour CDM-Tm Elite Mini

MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

Mini, single-ended, very high-efficiency, long-life Ceramic Metal Halide discharge lamp producing crisp white sparkling light with high color rendering

Product data

General Information	
Cap-Base	GU6.5 [GU6.5]
Bulb Shape	T-4
Operating Position	UNIVERSAL [Any or Universal (U)]
Life To 5% Failures (Nom)	12000 h
Life To 10% Failures (Nom)	14000 h
Life To 20% Failures (Nom)	16000 h
Life To 50% Failures (Nom)	20000 h
ANSI Code HID	C156/E

Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Rated) (Min)	1620 lm
Luminous Flux (Rated) (Nom)	1800 lm
Color Designation	Warm White (WW)
Lumen Maintenance 1000 h (Nom)	91 %
Lumen Maintenance 12000 h (Nom)	77 %
Lumen Maintenance 10000 h (Nom)	78 %
Lumen Maintenance 2000 h (Nom)	87 %
Lumen Maintenance 4000 h (Nom)	84 %
Lumen Maintenance 5000 h (Nom)	83 %

Chromaticity Coordinate X (Nom)	0.436
Chromaticity Coordinate Y (Nom)	0.396
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	90 lm/W
Color Rendering Index (Min)	81
Color Rendering Index (Nom)	84

Operating and Electrical	
Power (Rated) (Nom)	20.0 W
Lamp Current Run-Up (Max)	0.5 A
Re-Ignition Time (Min) (Max)	15 min
Ignition Time (Max)	30 s
Voltage (Max)	100 V
Voltage (Min)	90 V
Voltage (Nom)	95 V

Controls and Dimming	
Dimmable	No
Run-Up Time 90% (Max)	3 min

MASTERCLOUR CDM-Tm Elite Mini


Mechanical and Housing	
Bulb Finish	Clear
Approval and Application	
Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	3.5 mg
Energy Consumption kWh/1000 h	22 kWh
UV	
Pet (Niosh) (Min)	8 h/500lx
Damage Factor D/fc (Max)	0.5
Luminaire Design Requirements	
Bulb Temperature (Max)	380 °C

Cap-Base Temperature (Max)	250 °C
Product Data	
Full product code	872790089083900
Order product name	MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT
EAN/UPC - Product	8727900890839
Order code	928183505130
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928183505130
Net Weight (Piece)	0.007 kg
ILCOS Code	MT/UB-20/830-H-GU6.5-13.3/52

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- For 50W use with Philips electronic gear only
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



CDM-Tm 20W/830 GU6.5

Product	D	D	O	L	L	L	C
MC CDM-Tm Elite Mini 20W/830	13.3 mm	0.5 in	3.4 mm	28 mm	32 mm	30 mm	56.7 mm
GU6.5 1CT							

MASTERColour CDM-Tm Elite Mini

Photometric data

