





Наименование	Артикул (EAN10)	Замена для <sup>2</sup>	Лм	Лм/Вт		L70 <sup>3</sup>	ДхШхВ, мм ØхВ, мм	 <sup>4</sup>
<b>LANTERN</b>								
O Facade Lantern 12W/3000K GY IP54	4058075074835	40 W GLS	610	50	210	30000	176x110x240	
O BD 500 Lantern 12W/3000K GY IP54	4058075074859	40 W GLS	610	50	210	30000	110x500	
O BD 900 Lantern 12W/3000K GY IP54	4058075074873	40 W GLS	610	50	210	30000	110x900	
<b>EDGE</b>								
O Facade Edge 12W/3000K GY IP54	4058075074750	60 W GLS	740	60	107	30000	168x100x273	
O Facade Edge 12W/3000K WT IP54	4058075074774	60 W GLS	770	65	107	30000	168x100x273	
O Facade Edge 12W/3000K GY S IP54	4058075074798	60 W GLS	740	60	107	30000	168x100x273	✓
O Facade Edge 12W/3000K WT S IP54	4058075074811	60 W GLS	770	65	107	30000	168x100x273	✓
<b>UPDOWN</b>								
O Facade Updown 12W/3000K GY IP54	4058075075054	60 W GLS	700	60	280	30000	55x90x160	
O Facade Updown 12W/3000K WT IP54	4058075075078	60 W GLS	710	60	280	30000	55x90x160	
<b>BELT</b>								
O Facade Belt RD 11W/3000K GY IP54	4058075074972	40 W GLS	400	38	335	30000	60x240x142	
O Facade Belt SQ 11W/3000K GY IP54	4058075074996	40 W GLS	410	39	340	30000	60x240x142	
<b>SPOT</b>								
O Facade Spot 8W/3000K GY IP54	4058075074712	40 W GLS	440	55	110	30000	135x90x140	
O Facade Spot 8W/3000K WT IP54	4058075074736	40 W GLS	460	60	110	30000	135x90x140	
<b>ROUND &amp; SQUARE</b>								
O Surface RD 13W/3000K GY IP54	4058075074897	40 W GLS	480	35	100	30000	202x45	
O Surface RD 13W/3000K WT IP54	4058075074910	40 W GLS	600	45	100	30000	202x45	
O Surface SQ 13W/3000K GY IP54	4058075074934	40 W GLS	480	35	100	30000	202x202x45	
O Surface SQ 13W/3000K WT IP54	4058075074958	40 W GLS	600	45	100	30000	202x202x45	
<b>INDIRECT</b>								
O Facade IND RD 13W/3000K GY IP54	4058075075016	40 W GLS	480	35	240	30000	150x118	
O Facade IND RD 13W/3000K WT IP54	4058075075030	60 W GLS	640	50	240	30000	150x118	

<sup>1</sup> Для получения подробной информации об условиях гарантии см. [www.ledvance.com.ru/guarantee](http://www.ledvance.com.ru/guarantee) | <sup>2</sup> Замена традиционных эквивалентов | <sup>3</sup> t [h]: L70 @ 25°C (Ta) | <sup>4</sup> Датчик движения и дневного света