



product details

44865 WFL

Product description: 44865 WFL
 Product code: 4050300531533
 Quantity: Shipping carton box (VS) contains 20 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300531533

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
SEG number	8327014
ILCOS	HRGS//UB-35-12-GU5,3-51/36

General Description	
Base (standard designation)	GU5.3
Mercury-free	Yes

Technical - Electrical Data	
Nominal wattage (packaging)	35 W
Construction wattage	35 W
Nominal voltage	12 V

Technical - Geometries	
Overall length	46.00 mm
Contact spacing	5.3 mm
Diameter	51.0 mm
Length	46.00 mm

Technical - Lifespan	
Nominal lamp life time	3000 h
Rated lamp life time	3000 h

Technical - Light Technical Data	
Rated color rendering index Ra	100
Luminous intensity	1000 cd
Beam angle	36 °
Color temperature	3000 K
Rated color temperature	3000 K
Color rendering index Ra	100
Rated starting time	0.0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300272634	Folding carton box contains 1 Piece	46,000 mm x 46,000 mm x 58,000 mm	39,500 g (0,000 g)	0.123 Cubic dec.
4050300531533	Shipping carton box contains 20 Piece	158,000 mm x 123,000 mm x 191,000 mm	866,000 g (0,000 g)	3.074 Cubic dec.





product details

44865 WFL

Every professional knows that light is not always the same when it comes to illuminating heat-sensitive objects. In this case the DECOSTAR 51 dichroic reflector lamp is the right choice because most of the heat produced by the lamp is emitted through the rear of the reflector. This reduces the heat in the light beam by up to 66 %. It is therefore easier to present heat-sensitive objects in the right light.

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Approved for use in open luminaires to IEC 60598-1
- Average life: 2,000 h
- Dimmable
- $R_a=100$
- Color temperature: 20 W - 2,800 K; 35 W - 2,900 K; 50 W - 2,950 K
- Base: GU5.3
- UV filter

For light distribution curves go to www.osram.com