



product details

**64425**

Product description: 64425  
 Product code: 4050300942261  
 Quantity: Shipping carton box (VS) contains  
 40 Piece (PCE)

You can find this product in the eCatalog:

[http://catalog.myosram.com?~language=EN&~country=DE&it\\_p=4050300942261](http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300942261)

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
SEG number	8326554
ILCOS	HSGST/C/UB-20-12-G4-10/22

General Description	
Base (standard designation)	G4
Filament setting	Transversal
Mercury-free	Yes
Rated lamp mercury content	0.0 mg

Technical - Electrical Data	
Nominal wattage (packaging)	20 W
Construction wattage	20 W
Nominal voltage	12 V
Rated number of switching cycles	1000000 <sup>1)</sup>
Rated power factor $\lambda$	1.00

Technical - Geometries	
Overall length	33.00 mm
Contact spacing	4 mm
Diameter	10 mm
Length	33.00 mm
Light center length (LCL)	22 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Rated color rendering index Ra	100
Luminous flux	320 lm
Nominal luminous flux	320 lm
Rated luminous flux	320 lm
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2800 K
Rated color temperature	2800 K
Color rendering index Ra	100
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s



product details

64425

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300003924	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	19,778 g (0,000 g)	0,040 Cubic dec.
4050300942261	Shipping carton box contains 40 Piece	121,000 mm x 107,000 mm x 144,000 mm	202,625 g (0,000 g)	1,864 Cubic dec.

**Lighting solutions that are unlike anything else - that's HALOSTAR from OSRAM. Open halogen lighting systems and unshielded luminaires are no longer a problem. These decorative reliable point light sources bring rooms to life. It is now possible to design, create and present in the finest detail.**

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires to IEC 60598-1
- Average life: 2,000 h
- Dimmable
- Ra=100
- Color temperature: 10 W/20 W - 2,800 K; 35 W - 2,900 K; 50 W - 3,000 K
- Base: G4, GY6.35
- UV filter

<sup>1)</sup> At 1 s on / 1 s off