

Прямая секция без точек отвода



Назначение:

- передача электроэнергии.

Характеристики:

- степень защиты IP55, возможно увеличение до IP65;
- возможность изготовления произвольной длины по инструкции;
- рабочая температура изоляции – 155 °С;
- напряжение пробоя – 12 кВ;
- изоляция не содержит галогенов;
- корпус из алюминия с порошковой окраской может применяться в качестве нулевого защитного проводника.

Номинальный ток, А	Материал шины	Высота корпуса, мм	3P+N L=3000 мм	3P+N L=500-2999 мм	3P+N+Fe/2 L=3000 мм	3P+N+Fe/2 L=500-2999 мм	3P+N+Fe L=3000 мм	3P+N+Fe L=500-2999 мм
630	алюминий	96,8	PTA06ESEF1AA	PTA06ESEF2AA	PTA06ISEF1AA	PTA06ISEF2AA	PTA06GSEF1AA	PTA06GSEF2AA
800		96,8	PTA08ESEF1AA	PTA08ESEF2AA	PTA08ISEF1AA	PTA08ISEF2AA	PTA08GSEF1AA	PTA08GSEF2AA
1000		116,8	PTA10ESEF1AA	PTA10ESEF2AA	PTA10ISEF1AA	PTA10ISEF2AA	PTA10GSEF1AA	PTA10GSEF2AA
1250		136,8	PTA13ESEF1AA	PTA13ESEF2AA	PTA13ISEF1AA	PTA13ISEF2AA	PTA13GSEF1AA	PTA13GSEF2AA
1600		196,8	PTA16ESEF1AA	PTA16ESEF2AA	PTA16ISEF1AA	PTA16ISEF2AA	PTA16GSEF1AA	PTA16GSEF2AA
2000		236,8	PTA20ESEF1AA	PTA20ESEF2AA	PTA20ISEF1AA	PTA20ISEF2AA	PTA20GSEF1AA	PTA20GSEF2AA
2500		276,8	PTA25ESEF1AA	PTA25ESEF2AA	PTA25ISEF1AA	PTA25ISEF2AA	PTA25GSEF1AA	PTA25GSEF2AA
3200		362,3	PTA32ESEF1AA	PTA32ESEF2AA	PTA32ISEF1AA	PTA32ISEF2AA	PTA32GSEF1AA	PTA32GSEF2AA
4000		442,3	PTA40ESEF1AA	PTA40ESEF2AA	PTA40ISEF1AA	PTA40ISEF2AA	PTA40GSEF1AA	PTA40GSEF2AA
5000		522,3	PTA50ESEF1AA	PTA50ESEF2AA	PTA50ISEF1AA	PTA50ISEF2AA	PTA50GSEF1AA	PTA50GSEF2AA
800	медь	96,8	PTC08ESEF1AA	PTC08ESEF2AA	PTC08ISEF1AA	PTC08ISEF2AA	PTC08GSEF1AA	PTC08GSEF2AA
1000		96,8	PTC10ESEF1AA	PTC10ESEF2AA	PTC10ISEF1AA	PTC10ISEF2AA	PTC10GSEF1AA	PTC10GSEF2AA
1250		116,8	PTC13ESEF1AA	PTC13ESEF2AA	PTC13ISEF1AA	PTC13ISEF2AA	PTC13GSEF1AA	PTC13GSEF2AA
1600		136,8	PTC16ESEF1AA	PTC16ESEF2AA	PTC16ISEF1AA	PTC16ISEF2AA	PTC16GSEF1AA	PTC16GSEF2AA
2000		196,8	PTC20ESEF1AA	PTC20ESEF2AA	PTC20ISEF1AA	PTC20ISEF2AA	PTC20GSEF1AA	PTC20GSEF2AA
2500		236,8	PTC25ESEF1AA	PTC25ESEF2AA	PTC25ISEF1AA	PTC25ISEF2AA	PTC25GSEF1AA	PTC25GSEF2AA
3200		276,8	PTC32ESEF1AA	PTC32ESEF2AA	PTC32ISEF1AA	PTC32ISEF2AA	PTC32GSEF1AA	PTC32GSEF2AA
4000		362,3	PTC40ESEF1AA	PTC40ESEF2AA	PTC40ISEF1AA	PTC40ISEF2AA	PTC40GSEF1AA	PTC40GSEF2AA
5000		442,3	PTC50ESEF1AA	PTC50ESEF2AA	PTC50ISEF1AA	PTC50ISEF2AA	PTC50GSEF1AA	PTC50GSEF2AA
6400		522,3	PTC64ESEF1AA	PTC64ESEF2AA	PTC64ISEF1AA	PTC64ISEF2AA	PTC64GSEF1AA	PTC64GSEF2AA