



# MSR Hot Restrike

## MSR 4000 HR 1CT/1

Thanks to an optimized color temperature and a high color rendering index, the MSR Hot Restrike creates perfect 'daylight' in any condition. Also, the single ended lamp design enables hot re-ignition, which ensures daylight lighting and superb color rendition is always instantly available. They also incorporate the innovative P3 technology, developed by Philips, which allows use at higher temperatures and therefore extends lifetime and consistency of high-quality light output.

### Product data

General Information		Ignition Supply Voltage (Min)	
Cap-Base	G38 [ G38]		342 V
Operating Position	UNIVERSAL [ Any or Universal (U)]	Controls and Dimming	
Main Application	Indoor & Outdoor filming	Dimmable	Yes
Life To 50% Failures (Nom)	500 h	Mechanical and Housing	
System Description	Hot Restrike	Cap-Base Information	-
Light Technical		Luminaire Design Requirements	
Color Code	- [ Not Specified]	Bulb Temperature (Max)	700 °C
Luminous Flux (Nom)	380000 lm	Pinch Temperature (Max)	450 °C
Chromaticity Coordinate X (Nom)	304	Product Data	
Chromaticity Coordinate Y (Nom)	310	Full product code	872790092676700
Correlated Color Temperature (Nom)	7270 K	Order product name	MSR 4000 HR 1CT/1
Luminous Efficacy (rated) (Nom)	95 lm/W	EAN/UPC - Product	8727900926767
Color Rendering Index (Nom)	91	Order code	928050405114
Operating and Electrical		Numerator - Quantity Per Pack	1
Power (Rated) (Nom)	4000 W	Numerator - Packs per outer box	1
Lamp Current (Nom)	27.5 A	Material Nr. (12NC)	928050405114


# MSR Hot Restrike

Net Weight (Piece)	0.356 kg
--------------------	----------

## Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

## Dimensional drawing



Product	D	O	L	L	L	C	F	F	F
MSR 4000 HR	77 mm	20.0	141	143	142	255	67 mm	65 mm	63 mm
1CT/1		mm	mm	mm	mm	mm			

MSR 4000 HR

## Photometric data

