



product details

**64784**



Product description: 64784  
 Product code: 4050300214481  
 Quantity: Shipping carton box (VS) contains 12 Piece (PCE)

You can find this product in the eCatalog:  
[http://catalog.myosram.com?~language=EN&~country=DE&it\\_p=4050300214481](http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300214481)

Applications	
Dimmable	Yes
Burning position	horizontal
Fuse, quick-acting	10.0 A

Categorizations	
SEG number	8327708
ILCOS	HDG-2000-230-R7s-327,4

Certificates & Standards	
EEl - Energy Label	F

General Description	
Base (standard designation)	R7s
Mercury-free	Yes
Rated lamp mercury content	0.0 mg

Technical - Electrical Data	
Nominal wattage (packaging)	2 kW
Construction wattage	2000 W
Claimed equivalent incand. lamp power	2000 W
Nominal voltage	230 V
Rated number of switching cycles	1000000 <sup>1)</sup>
Rated power factor λ	1.00

Technical - Geometries	
Overall length	327.40 mm
Contact spacing	327.4 mm
Diameter	12 mm
Length	333.00 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Rated color rendering index Ra	100
Luminous flux	44000 lm
Nominal luminous flux	44000 lm
Rated luminous flux	44000 lm
Lumen main.fact.at end of nom.life time	0.80
Color temperature	3000 K
Rated color temperature	2900 K





product details

64784

Technical - Light Technical Data	
Color rendering index Ra	100
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300004204	Folding carton box contains 1 Piece	33,000 mm x 26,000 mm x 378,000 mm	48,000 g (0,000 g)	0,314 Cubic dec.
4050300214481	Shipping carton box contains 12 Piece	96,000 mm x 129,000 mm x 395,000 mm	596,200 g (0,000 g)	4,867 Cubic dec.

**HALOLINE from OSRAM is a double-ended halogen lamp for line voltage. The extensive range covering wattages from 60 to 2,000 W and luminous flux from 840 to 44,000 lm can be used in a wide range of applications. These include outdoor lighting, indoor shop lighting and shop windows. HALOLINE is also ideal for indirect lighting in the home.**

- Brilliant accent light
- Ideal for emphasizing and accentuating the structure of a room
- Direct replacement for standard tubular halogen lamps
- No transformer required
- Average life: 2,000 h
- Dimmable
- $R_a=100$
- Color temperature: 3,000 K
- Burning position: universal - 60 W; horizontal - 750 W...2,000 W
- Base: R7s

<sup>1)</sup> At 1 s on / 1 s off