

**Описание:**

- Устойчивы к УФ-излучению и высоким температурам (до 85°C).
- Разные цвета

**Материалы:**

- Полиамид (нейлон 6/6), UL 94V-2

<b>№, 100 шт./упак</b>	<b>Д x Ш мм</b>	<b>Толщина, мм</b>	<b>Макс. Ø пучка, мм</b>	<b>Мин. предел прочности на разрыв, кг</b>	<b>Инструмент</b>
GT-100M (1000 шт.) GT-100MC GT-100MBC GT-100MC-TF	100 x 2,5	1,1	22	8,1	HT-519 HT-218 HT-2018
GT-140MC	140 x 2,5	1,1	33	8,1	HT-519 HT-218 HT-2018
GT-200MC	200 x 2,5	1,2	53	8,1	HT-519 HT-218 HT-2018
GT-150IC GT-150IBC GT-150IBUVC GT-150IC-TF	150 x 3,6	1,2	35	18,2	HT-519 HT-218 HT-2018
GT-180I-TF	180 x 3,6				HT-519 HT-218 HT-2018
GT-190ST-TF	190 x 4,8				HT-519 HT-218 HT-2018
GT-200ST-TF	200 x 4,8				HT-519 HT-218 HT-2018
GT-200IC GT-200IBC GT-200I-TF	200 x 3,6	1,3	53	18,2	HT-519 HT-218 HT-2018
GT-250IC GT-250IBC GT-250IBUVC	250 x 3,6	1,2	65	18,2	HT-519 HT-218 HT-2018
GT-300HD-TF GT-300ST-TF	300 x 7,3 300 x 4,8				HT-519 HT-218 HT-2018

GT-300IC GT-300IBC	300 x 3,6	1,25	76	18,2	HT-519 HT-218 HT-2018
GT-370HD-TF GT-370IBC	370 x 3,6				HT-519 HT-218 HT-2018
GT-370IC GT-370IBC GT-370IBUVC	370 x 3,6	1,3	102	18,2	HT-519 HT-218 HT-2018
GT-430STBC	430 x 3,6	1,3	110	22,2	HT-519 HT-218 HT-2018
GT-430HD-TF	435 x 9				HT-519 HT-218 HT-2018
GT-450ST	450 x 4,8	1,4	116	22,2	HT-519 HT-218 HT-2018
GT-530ST	530 x 4,8	1,4	140	22,2	HT-519 HT-218 HT-2018
GT-630HD	609 x 9,0	1,8	179	79,4	HT-519 HT-2018
GT-710HD	710 x 9,0	1,8	190	79,4	HT-519 HT-2018
GT-830HD	812 x 9,0	1,8	239	79,4	HT-519 HT-2018
GT-920HD	912 x 9,0	1,8	263	79,4	HT-519 HT-2018
GT-1020HD	1020 x 9,0	1,8	295	79,4	HT-519 HT-2018
GT-1220HD	1220 x 9,0	1,8	365	79,4	HT-519 HT-2018
GT-1530HD Упак.50шт./упак	1530 x 9,0	1,8	460	79,4	HT-519 HT-2018