



product details

DULUX S/E 11 W/827



Product description: DULUX S/E 11 W/827
 Product code: 4050300251295
 Quantity: Shipping carton box (VS) contains 10 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300251295

Applications	
Suitable for indoor	Yes

Categorizations	
SEG number	8330064

Certificates & Standards	
EEI - Energy Label	A

General Description	
Rated lamp mercury content	1.4 mg
Base (standard designation)	2G7
Recycling	Yes

Technical - Electrical Data	
Construction wattage	11 W
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body
Rated lamp efficacy (standard condition)	82 lm/W
Nominal wattage (packaging)	11 W

Technical - Geometries	
Overall length	214.00 mm
Tube diameter	12 mm
Length	214.00 mm
Length acc. to IEC standard	215 mm
Construction length	214.00 mm

Technical - Lifespan	
Rated lamp life time	20000 h
Nominal lamp life time	20000 h
Operation mode LLMF/LSF	50 Hz
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.85

Technical - Light Technical Data	
Rated color rendering index Ra	80-89
Luminous flux at 25 °C	900 lm
Nominal luminous flux	900 lm
Rated luminous flux	900 lm
Luminous flux	900 lm
Light color	827



01.08.2011

Subject to change without notice. Errors and omission excepted.

© 2011 OSRAM AG

Page 1 of 2



product details

DULUX S/E 11 W/827

Technical - Light Technical Data

Rated color temperature	2700 K
Color rendering index Ra	80...89
Light color as per EN 12464-1	LUMILUX INTERNA
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.78
Rated LLMF at 6,000 h	0.76
Rated LLMF at 8,000 h	0.76
Color rendering group	1B
Color temperature	2700 K

Technical - Temperatures

Rated ambient temp.w.max.luminous flux	25.0 °C
--	---------

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300017662	Folding carton box contains 1 Piece	39,000 mm x 23,000 mm x 229,000 mm	44,800 g (0,000 g)	0,205 Cubic dec.
4050300251295	Shipping carton box contains 10 Piece	155,000 mm x 203,000 mm x 99,000 mm	508,000 g (0,000 g)	2,646 Cubic dec.

These innovative energy-saving lamps can be operated on battery, solar or mains power. They are also fully dimmable. Their dimensions and wattages are identical to those of the successful standard OSRAM DULUX S models.

- Comfortable light in ECG operation
- Small dimensions, extremely slim
- Smallest unit suitable for solar or battery-powered systems (emergency power)
- Low power consumption (7 W, 9 W, 11 W)
- Single-ended 4-pin plug-in 2G7 base