

Трубчатые кабельные наконечники с насечками, стандартная серия 90°


HUPtype

- из трубки, отожжённый материал • поверхность: лужёная
- материал: 99,9% электролитная медь E-CU DIN 40500
- для многожильных кабелей круглого сечения, напр., VDE 0295 класс 2
- для кругло-сжатых секторных проводов



Cu

№ арт.	псп	M	d2	d1	d4	A	v1	v2	Д	B	c1	c2	Kr/100	YE
290966/90	35	6	6,5	8,5	12,0	17,0	2	1	32,0	17,0	7,5	7,5	1,900	240 40
290968/90		8	8,5	8,5	12,0	17,0	2	1	34,0	17,0	10,0	10,0	1,900	240 40
290970/90		10	10,5	8,5	12,0	17,0	2	1	37,0	19,0	12,0	12,0	2,100	160 40
290972/90		12	13,0	8,5	12,0	17,0	2	1	38,0	21,0	13,0	13,0	2,000	160 40
290976/90	50	6	6,5	10,0	14,0	19,0	2	1	37,0	20,0	10,0	10,0	2,900	160 40
290978/90		8	8,5	10,0	14,0	19,0	2	1	37,0	20,0	10,0	10,0	2,700	160 40
290980/90		10	10,5	10,0	14,0	19,0	2	1	39,0	20,0	12,0	12,0	2,900	150 25
290982/90		12	13,0	10,0	14,0	19,0	2	1	43,0	23,0	13,0	13,0	3,300	100 25
290986/90	70	8	8,5	12,0	16,5	21,0	2	1	43,0	23,0	10,0	10,0	4,200	100 25
290988/90	*	10	10,5	12,0	16,5	21,0	2	1	44,0	23,0	12,0	12,0	4,300	100 25
290990/90		12	13,0	12,0	16,5	21,0	2	1	46,0	23,0	13,0	13,0	4,500	100 25
290992/90		16	17,0	12,0	16,5	21,0	2	1	50,0	28,0	16,0	16,0	5,100	100 25
290994/90	95	8	8,5	13,5	18,0	25,0	2	1	48,0	26,0	12,0	12,0	5,300	100 25
290996/90		10	10,5	13,5	18,0	25,0	2	1	48,0	26,0	12,0	12,0	5,100	100 25
290998/90		12	13,0	13,5	18,0	25,0	2	1	49,0	26,0	13,0	13,0	5,200	100 25
291000/90		16	17,0	13,5	18,0	25,0	2	1	54,0	28,0	16,0	16,0	5,600	60 15
291002/90		20	21,0	13,5	18,0	25,0	2	1	60,0	36,0	22,0	22,0	6,000	60 15
290006/90	120	10	10,5	15,0	19,5	26,0	2	1	51,0	28,0	14,0	14,0	6,200	60 15
290008/90		12	13,0	15,0	19,5	26,0	2	1	51,0	28,0	14,0	14,0	6,100	60 15
290010/90		16	17,0	15,0	19,5	26,0	2	1	54,0	30,0	16,0	16,0	6,200	60 15
290014/90	150	10	10,5	16,5	21,0	30,0	2	1	56,0	31,0	14,0	14,0	7,500	72 15
290016/90		12	13,0	16,5	21,0	30,0	2	1	57,0	31,0	15,0	15,0	7,300	72 15
290018/90		16	17,0	16,5	21,0	30,0	2	1	58,0	31,0	16,0	16,0	7,500	48 15
290020/90		20	21,0	16,5	21,0	30,0	2	1	66,0	36,0	22,0	22,0	8,800	48 12
291004/90	185	10	10,5	19,0	24,0	30,0	2	1	65,0	35,0	18,0	18,0	11,100	40 20
290022/90		12	13,0	19,0	24,0	30,0	2	1	65,0	35,0	18,0	18,0	11,100	40 20
290024/90		16	17,0	19,0	24,0	30,0	2	1	65,0	35,0	18,0	18,0	10,700	40 20
290028/90	240	12	13,0	21,0	26,0	35,0	4	2	72,0	39,0	21,5	19,0	13,700	30 15
290030/90		16	17,0	21,0	26,0	35,0	4	2	72,0	39,0	21,5	19,0	13,400	30 15



Стыковые соединители, стандартная серия


HUPtype

- из трубки, отожжённый материал • поверхность: лужёная
- материал: 99,9% электролитная медь E-CU DIN 40500
- для многожильных кабелей круглого сечения, напр., VDE 0295 класс 2
- для кругло-сжатых секторных проводов



Cu

№ арт.	псп	d1	d4	v1	v2	Од	Kr/100	YE
291050	0,75	1,3	2,8	1	-	14	0,051	2000 100
291052	1,5	1,8	3,3	1	-	14	0,074	2000 100
291054	2,5	2,3	4,2	1	-	16	0,150	2000 100
291056	4	3,0	5,0	1	-	19	0,195	1000 100
291058	6	3,5	6,5	1	-	19	0,350	1000 100
291060	10	4,5	7,0	1	-	30	0,558	600 100
291062	16	5,5	8,5	1	1	35	0,984	500 50
291064	25	7,0	10,0	2	1	40	1,350	200 50
291066	35	8,5	12,0	2	1	45	2,150	200 50
291068	50	10,0	14,0	2	1	50	3,100	100 25
291070	70	12,0	16,5	2	1	55	4,700	50 25
291072	95	13,5	18,0	2	1	60	5,600	50 25
291074	120	15,0	19,5	2	1	65	6,800	50 15
291076	150	16,5	21,0	2	1	70	7,800	50 20
291078	185	19,0	24,0	2	1	80	11,700	36 5
291080	240	21,0	26,0	4	2	90	13,900	12 10
291082	300	23,5	29,5	4	2	100	22,300	6 5
291084	400	27,0	34,0	4	2	100	29,000	6 5



haura®

... решения которые убеждают

HAUPA GmbH & Co. KG, Königstr. 165-169, 42853 Remscheid, телефон: +49 (0)2191 8418-0, факс: +49 (0)2191 8418-840, sales@haura.com