

# **DULUX D 10 W/830 G24D-1**

OSRAM DULUX D | CFLni, 2 tubes, with 2-pin base for CCG operation



- Offices, public buildings
- Shops
- · Hotels, restaurants
- Industrial lighting

#### **Product benefits**

- · Very economical
- Good quality of light
- Very good luminous flux
- · Long service life
- Improved maintenance

#### **Product features**

- Short and compact pin-base lamp with double-turn tubes
- · Average life: 10,000 h
- Color rendering index R<sub>a</sub>: 80...89
  Single-ended two-pin plug-in GX24d base





## **Technical data**

#### **Electrical data**

Nominal wattage	10 W
Rated wattage	10 W


## Light technical data


Color rendering index Ra	8089
Rated luminous flux	600 lm
Luminous flux at 25 °C	600 lm
Light color	830
Color temperature	3000 K
Nominal luminous flux	600 lm
Light color as per EN 12464-1	LUMILUX Warm White
Luminance	4 cd/cm <sup>2</sup>

## **Dimensions & weight**

Tube diameter	12 mm
Length	110.0 mm
Length acc. to IEC standard	95 mm
Length with base excl. base pins/connection	87.00 mm







Product line drawing with letters

Base

### Colors & materials

Lamp mercury content 1.	1.4 mg
-------------------------	--------

### **Temperatures**

Rated ambient temp.w.max.luminous flux	25.0 °C

## Lifespan

Service life	6500 h
Operation mode LLMF/LSF	50 Hz
Lifespan	10000 h <sup>1)</sup>

<sup>1)</sup> With CCG/LLCG

### Additional product data

Base (standard designation)	G24d-1

## Product datasheet



## Additional product data

Appropriate disposal acc. to WEEE	Yes
-----------------------------------	-----

## Capabilities

Suitable for indoor	Yes
---------------------	-----

## Certificates & standards

EEI – Energy Label	В





# **Equipment / Accessories**

ullet Suitable for operation on conventional control gear

# Safety advice

In case of lamp breakage: www.osram.com/brokenlamp





Circuit diagram

Circuit diagram



# **Logistical Data**

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4050300025681	Folding carton box 1	36 mm x 36 mm x 120 mm	47.40 g	0.16 dm³
4050300257952	Shipping carton box 10	112 mm x 120 mm x 164 mm	478.00 g	2.20 dm <sup>3</sup>

## Product datasheet



## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.