



product details

L 58W/840

Product description: L 58W/840
Product code: 4050300517964
Quantity: Shipping carton box (VS) contains
25 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300517964

Applications	
Suitable for indoor	Yes

Categorizations	
SEG number	8329118

Certificates & Standards	
EEl - Energy Label	A

General Description	
Base (standard designation)	G13
Recycling	Yes
Rated lamp mercury content	4.5 mg

Technical - Electrical Data	
Nominal wattage (packaging)	58 W
Construction wattage	58 W
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body

Technical - Geometries	
Tube diameter	26 mm
Diameter	26.00 mm
Length	1500.00 mm
Length with base excl. base pins/connect	1500 mm

Technical - Lifespan	
Lifespan	20000 h ¹⁾
Service life	18000 h ²⁾
Operation mode LLMF/LSF	50 Hz

Technical - Light Technical Data	
Luminous flux at 25 °C	5200 lm
Luminous flux	5200 lm
Light color	840
Rated color temperature	4000 K
Color rendering index Ra	80...89
Light color as per EN 12464-1	LUMILUX Cool White

Technical - Temperatures	
Rated ambient temp.w.max.luminous flux	25.0 °C



Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300517957	Sleeves contains 1 Piece	33,000 mm x 27,000 mm x 1.515,000 mm	242,000 g (0,000 g)	1,274 Cubic dec.
4050300517964	Shipping carton box contains 25 Piece	145,000 mm x 320,000 mm x 1.368,000 mm	6.520,000 g (0,000 g)	32,641 Cubic dec.

Fluorescent lamps in LUMILUX and BASIC light colors offer up to 10 % energy savings compared with previous fluorescent lamps with a 38 mm tube diameter. They are designed to operate with conventional control gear and starters or with QUICKTRONIC electronic control gear. If used in starter circuits, these lamps can operate with standard control gear and recommended compensation capacitors.

For more information go to www.osram.com/system-guarantee, www.osram.com/QUICKTRONIC

- 1) With preheat ECG
- 2) With preheat ECG