



product details

DULUX D 26 W/840

Product description: DULUX D 26 W/840
 Product code: 4050300245386
 Quantity: Shipping carton box (VS) contains 10 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300245386

Applications	
Suitable for indoor	Yes

Categorizations	
SEG number	8330148

Certificates & Standards	
EEI - Energy Label	B

General Description	
Rated lamp mercury content	2.6 mg
Base (standard designation)	G24d-3
Recycling	Yes

Technical - Electrical Data	
Construction wattage	26 W
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body
Rated lamp efficacy (standard condition)	69 lm/W
Nominal wattage (packaging)	26 W

Technical - Geometries	
Overall length	172.00 mm
Diameter	11.00 mm
Tube diameter	12 mm
Length with base excl. base pins/connect	149 mm
Length	172.00 mm
Length acc. to IEC standard	160 mm
Construction length	172.00 mm

Technical - Lifespan	
Operation mode LLMF/LSF	50 Hz
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.85

Technical - Light Technical Data	
Nominal luminous flux	1800 lm
Rated color rendering index Ra	>=80
Luminous flux at 25 °C	1800 lm
Rated luminous flux	1800 lm
Luminous flux	1800 lm
Light color	840



28.07.2011

Subject to change without notice. Errors and omission excepted.

© 2011 OSRAM AG

Page 1 of 2



product details

DULUX D 26 W/840

Technical - Light Technical Data

Rated color temperature	4000 K
Color rendering index Ra	80...89
Light color as per EN 12464-1	LUMILUX Cool White
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.78
Rated LLMF at 6,000 h	0.76
Rated LLMF at 8,000 h	0.76
Color rendering group	1B
Color temperature	4000 K

Technical - Temperatures

Rated ambient temp.w.max.luminous flux	25.0 °C
--	---------

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300012049	Folding carton box contains 1 Piece	36,000 mm x 36,000 mm x 180,000 mm	68,167 g (0,000 g)	0,233 Cubic dec.
4050300245386	Shipping carton box contains 10 Piece	127,000 mm x 187,000 mm x 150,000 mm	722,294 g (0,000 g)	2,893 Cubic dec.

This compact fluorescent lamp is ideal for miniature luminaires and downlights for shallow recesses. They have twice the luminous flux and the same length as OSRAM DULUX S lamps. They provide a pleasant warm light and excellent color rendering.

- Lamp dimensions for luminaires with shallow mouting depth
- Single-ended plug-in base with integrated starter and RF suppression capacitor