



# Halogen reflector

## 6423FO 150W GZ6.35 15V 1CT/10X5F

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

### Product data


General Information		Operating and Electrical	
Cap-Base	GZ6.35 [ GZ6.35]	Power (Rated) (Nom)	150 W
Philips Code	6423FO	Voltage (Nom)	15 V
ANSI Code	EFR	Controls and Dimming	
LIF Code	A1/232	Dimmable	Yes
Bulb Shape	R50 [ R 50mm]	Mechanical and Housing	
Operating Position	P90/P15	Cap-Base Information	-
Main Application	Projection	Bulb Material	Quartz-UV Open
Life To 50% Failures (Nom)	50 h	Reflector Finish	-
J Code	-	Filament Shape	-
Light Technical		Filament Dimensions WxH	-
Correlated Color Temperature (Nom)	3380 K	Luminaire Design Requirements	
Color Rendering Index (Nom)	100	Bulb Temperature (Max)	900 °C

## Halogen reflector

Pinch Temperature (Max)	400 °C
Working Distance WD	32 mm
<b>Product Data</b>	
Full product code	871150040971360
Order product name	6423FO 150W GZ6.35 15V 1CT/10X5F
EAN/UPC - Product	8711500409713

Order code	924048218504
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924048218504
Net Weight (Piece)	0.024 kg

### Dimensional drawing



6423FO 150W GZ6.35 15V

Product	D	C
6423FO 150W GZ6.35 15V 1CT/10X5F	50 mm	42 mm

