

ENSTO

SLIW63

Зажим ответвительный перходной

Тип SLIW63
GTIN 6438100317812
Название Зажим ответвительный перходной
 Al/Cu 16-95 мм² / 2.5-25 мм²
Описание Предназначен для подключения
 изолированного провода ответвления к
 неизолированному проводу магистрали.
 Оснащен болтом со срывной головкой.



Техническая спецификация

Dimensions

Масса: 0.11 kg
Диаметр проводника мм: 4.0-14 / 3.0-10 mm
Магистраль мм²: 16 - 95 mm²
Проводник ответвления мм²: 2.5 - 25 mm²

Механические характеристики

Момент затяжки: 10.5±1.5 Nm

Ratings

ETIM 7: EC001062 Branch terminal

Specification

Use: Connection when using bare to insulated aluminium or copper conductors up to 1000 V AC.

Construction:

Construction:

Component	Material
Body and seal	Heat and UV resistant composite polymer and elastomer
Contact plate	Tin plated corrosion resistant aluminium alloy
Bolt	Coated stainless steel
Nut with shear-head	Aluminium alloy
Washer	Coated stainless steel
End-cap	UV resistant elastomer

Installation:

Unscrew the connector to have enough space for both conductors. Place the conductors into the grooves. Seal the end of the branch conductor with the end cap. Tighten the screw until the shear-head breaks.

Tools required:

13 mm hexagonal socket wrench, fork wrench ST34

Markings:

ENSTO, SLIW63, 16-95, 2.5-25, production date

Standard:

EN 50483-4

ETIM

ETIM

Nominal cross section main conductor, SM: 16 ... 95 mm²

Nominal cross section main conductor, SE: 16 ... 95 mm²

Material main conductor: Aluminium/copper

Nominal cross section branch conductor, SE/RE: 2.5 ... 25 mm²

Clamping channel opening main conductor: Both sides open

Surface protection: Tinned

Terminal insulated: true

Material branch conductor: Aluminium/copper

Type of connection: Insulation piercing connector IPC

Clamping channel opening branch conductor: Both sides open

Nominal cross section branch conductor, SM/RM: 2.5 ... 25 mm²

Упаковка

В стандартной упаковке

Unit:	PCS
Количество:	60
Длина:	385 mm
Ширина:	260 mm
Высота:	165 mm
Weight (net):	6.84 kg
Weight (brt):	7.107 kg

На палете

Unit:	PCS
Количество:	3240
Длина:	1200 mm
Ширина:	800 mm
Высота:	1140 mm
Weight (net):	369.36 kg
Volume:	1.0944

