

# CFL SQUARE 16 W/835 GR8

OSRAM CFL SQUARE 2 pins | Square CFLni with 2-pin base for CCG operation



- Low-profile wall and ceiling luminaires
- Public buildings, reception areas, offices, corridors, etc.
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

### **Product benefits**

- Square shape provides uniform distribution of light
- No shadows at either end and no dark patches
- Extremely low profile
- Very economical
- Good quality of light
- Long service life

### **Product features**

- Single-ended two-pin plug-in GR8 base
- Short and compact pin-base lamp with double-turn tubes
- Average life: 10,000 h
- Color rendering index R<sub>a</sub>: 80...89





### **Technical data**

#### Electrical data

Nominal wattage	16 W
Rated lamp efficacy (standard condition)	66 lm/W
Rated wattage	16 W

### Light technical data


Color rendering index Ra	8089
Rated luminous flux	1050 lm
Luminous flux at 25 °C	1050 lm
Light color	835
Color temperature	3500 К
Nominal luminous flux	1050 lm
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.78
Rated LLMF at 6,000 h	0.76
Rated LLMF at 8,000 h	0.75


#### **Dimensions & weight**


Length	138.0 mm <sup>1)</sup>
Length acc. to IEC standard	138 mm

<sup>1)</sup> Maximum










Product line drawing with letters

Base



Base

\_



#### Colors & materials

Lamp mercury content	5.0 mg

#### Lifespan

Service life	5000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.94
Rated lamp survival factor at 6,000 h	0.84
Rated lamp survival factor at 8,000 h	0.69
Operation mode LLMF/LSF	50 Hz
Lifespan	10000 h

### Additional product data

Base (standard designation)	GR8
Appropriate disposal acc. to WEEE	Yes

### Capabilities

Suitable for indoor

Yes

#### Certificates & standards

EEI – Energy Label	В
--------------------	---



## **Equipment / Accessories**

 $\boldsymbol{\cdot}$  Suitable for operation on conventional control gear

## Safety advice

In case of lamp breakage: www.osram.com/brokenlamp



## Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4050300816838	Folding carton box 1	152 mm x 34 mm x 152 mm	118.00 g	0.79 dm <sup>3</sup>
4050300816845	Shipping carton box 20	322 mm x 185 mm x 326 mm	2834.00 g	19.42 dm <sup>3</sup>



### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.