

ENSTO

SO276S

Зажим анкерный

Тип	SO276S
GTIN	6438100312008
Название	Зажим анкерный 4x(70-150) мм ² , со срывными головками
Описание	Анкерный зажим для СИП без отдельного несущего проводника. Болты оснащены гайками со срывными головками.

**Техническая спецификация****Dimensions**

Масса:	2.35 kg
Размер проводника:	4x70-120
Диаметр кабеля:	12.7-17.6

Электрические характеристики

Испытательное напряжение:	4 kV / 50 Hz / 1 min
---------------------------	----------------------

Механические характеристики

Минимальная разрывная нагрузка:	50 kN
Момент затяжки:	

Ratings

ETIM 7:	EC003516 Accessories for cross arm for utility pole
---------	---

Specification**Construction:**

Construction:

Component	Material
Steel parts	Hot-dip galvanised steel
Plastic parts	Fibreglass reinforced, frost, heat and UV-radiation resistant composite material
Shear-head nuts	aluminium alloy
Conical washers	Stainless steel

Installation:

Open the clamp and insert conductors between the wedges. Springs keep the clamp in an open position during the installation. Nuts must be tightened up uniformly until proper torque is reached. After reaching a proper torque retightening is not allowed.

Tools required:

Ratchet wrench CT164

Markings:

ENSTO, SO276S, 70-120 mm²

Standard:

EN 50483-2

ETIM**ETIM****Type of accessory:**

Other

Упаковка**В стандартной упаковке****Unit:**

PCS

Количество:

1